



UNITED LED UNITED (1274MM) 1X LED GI

Our Good Design Award-winning United luminaire continues to be a testament to the simple beauty of the fluorescent lamp. That being said, this LED-equipped luminaire is anything but ordinary, with a u-shaped housing that is both ceiling and wall-mountable. The light tubes of United are slightly recessed into the housing, emitting light on all sides, including the ends.

Art. Nr.13390002

SPECIFICATIONS

Lamp	1x 18.5W
Gear / Transfo	LED gear incl.
Weight	1.75kg
Min. distance	0.1 m
Power supply	230V
IP	IP20
Glow wire test	960°
Lifetime	L80 B10 @ 50.000 hrs
CRI	90
Lumen	926 Lm
Efficacy	42 Lm/W
UGR	25
Adjustability	Not Applicable

Available label
<http://supemodular.com/assets/TYPE2.pdf>



	WARM WHITE 2700K / CRI 90+	WARM WHITE 3000K / CRI 90+
black	13390002	13391002
white struc	13390009	13391009



UNITED LED UNITED (1274MM) 1X LED GI

ACCESSORIES	
COVER-PLATE	
13392032	UNITED COVER (1274MM) 1X BLACK STRUC
13392009	UNITED COVER (1274MM) 1X WHITE STRUC
SUSPENSION	
11060709	SUSPENSION KIT 4M - 3X 0.75 (2 CABLES) - WHITE STRUC
11060732	SUSPENSION KIT 4M - 3X 0.75 (2 CABLES) - BLACK STRUC
11061732	SUSPENSION KIT 4M - 5X 0.75 (2 CABLES) - BLACK STRUC
11061709	SUSPENSION KIT 4M - 5X 0.75 (2 CABLES) - WHITE STRUC

