



UNITED LED UNITED (1274MM) 2X LED DALI/PUSHDIM GI

Our Good Design Award-winning United luminaire continues to be a testament to the simple beauty of the fluorescent lamp. That being said, this LED-equipped luminaire is anything but ordinary, with a u-shaped housing that is both ceiling and wall-mountable. The light tubes of United are slightly recessed into the housing, emitting light on all sides, including the ends.

Art. Nr.13390509

SPECIFICATIONS

Lamp	2x 18.5W
Gear / Transfo	LED gear incl.
Weight	3.53kg
Min. distance	0.1 m
Power supply	230V
IP	IP20
Glow wire test	960°
Lifetime	L80 B10 @ 50.000 hrs
CRI	90
Lumen	2596 Lm
Efficacy	67 Lm/W
UGR	28
Adjustability	Not Applicable

Available label
<http://supemodular.com/assets/TYPE2.pdf>



	WARM WHITE 2700K / CRI 90+	WARM WHITE 3000K / CRI 90+
black	13390502	13391502
white struc	13390509	13391509



UNITED LED UNITED (1274MM) 2X LED DALI/PUSHDIM GI

ACCESSORIES	
SUSPENSION	
11065209	TWIN SUSPENSION KIT 4M 3X 0.75 (2 CABLES) - WHITE STRUC
11065232	TWIN SUSPENSION KIT 4M 3X0,75 [2 CABLES] BLACK STRUC
11065409	TWIN SUSPENSION KIT 4M 5X0,75 [2 CABLES] WHITE STRUC
11065432	TWIN SUSPENSION KIT 4M 5X0,75 [2 CABLES] BLACK STRUC
COVER-PLATE	
13392132	UNITED COVER (1274MM) 2X BLACK STRUC
13392109	UNITED COVER (1274MM) 2X WHITE STRUC

