


PUPIL 72 LED GE

Nothing short of the unexpected, Pupil is full of surprises and contradictions. Using nature as his muse, Dutch designer Basten Leijh created this organic, quirky shape: the downlighter that does the opposite. Nonconformity and functionality blend beautifully in our new family, and there's even more to it, than meets the eye.

Art. Nr. 11490032

SPECIFICATIONS

Lamp	1x LED Array		
Gear / Transfo	LED gear not incl.		
Cut-out size	ø 65 h 55		
Weight	0.26kg		
Min. distance	0.1 m		
IP	IP20		
Glow wire test	960°		
Lifetime	L80 B20 @ 50.000 hrs		
CRI	90		
CIE flux code	100/100/100/100/77		
Power supply	350mA	500mA	700mA
	8.5Vf	8.8Vf	9.1Vf
Connected load	3W	4,3W	6,4W
Lumen	265lm	357lm	461lm
Efficacy	88lm/W	81lm/W	72lm/W
UGR	17	18	19
Adjustability	h 360° v 60°		





Available label
<http://supemodular.com/assets/TYPE2.pdf>

	WARM WHITE 2700K / CRI 90+		WARM WHITE 3000K / CRI 90+	
	MEDIUM 25°	FLOOD 40°	MEDIUM 25°	FLOOD 40°
black struc	11490032	11490332	11490132	11490432
white struc	11490009	11490309	11490109	11490409



PUPIL 72 LED GE

ACCESSORIES	
ANTIGLARE	
14192032	SNOOT Ø26 BLACK
14191032	HONEYCOMB Ø26
14193032	CROSSBLADE Ø26 BLACK
HUE-BRIDGE	
70000616	HUE BRIDGE EU
70000617	HUE BRIDGE UK
HUE-DEVICE	
70000152	HUE DIMMER SWITCH
70000154	NIKO PURE SWITCH FOR HUE - WHITE STEEL
70000155	NIKO PURE SWITCH FOR HUE - BLACK STEEL
70000615	HUE TAP SWITCH
70008054	HUE SENSOR



Modular reserves the right to alter material, dimensions and characteristics without prior notice.
Lighting technology changes rapidly. Latest datasheet and documentation available on
www.supermodular.com.