

THIMBLE 74 ADJUSTABLE LED GE

Thimble roept tegelijk beelden op van minimalisme, verrassing en technologie. Subtiële rondingen, ietwat onthullende kleuren, kwalitatieve lens en leds. Met zijn diep verzonken, niet-verblindende lichtbron is Thimble dankzij de strakke, naadloze uitvoering een stille maar toch geraffineerde keuze voor chique woonruimtes of hotels/restaurants. Deze veelzijdige, elegante architecturale neerwaartse verlichting brengt pure vormen, definitie en kwalitatief licht in elke ruimte zonder alle aandacht naar zich toe te trekken.

| | WARM WHITE 2700K / CRI 90+ | WARM WHITE 3000K / CRI 90+ |
|-------------------|-------------------------------|-------------------------------|
| | MEDIUM 30° | MEDIUM 30° |
| ano black | 11621081 | 11621181 |
| ano bronze | 11621082 | 11621182 |
| ano champagne | 11621041 | 11621141 |
| ano gold | 11621042 | 11621142 |
| ano silver bronze | 11621084 | 11621184 |
| black struc | 11621032 | 11621132 |
| white struc | 11621009 | 11621109 |

Art. Nr. 11621184

SPECIFICATIES

| | | |
|--------------------|--------------------|--------|
| Lamp | 1x LED Array | |
| Gear / Transfo | LED gear not incl. | |
| Inbouwopening | ø 70 h 110 | |
| Gewicht | 0.2kg | |
| Min. afstand | 0.1 m | |
| IP | IP20 | |
| Gloeidraadtest | 960° | |
| Levensduur | 50000 hrs | |
| CRI | 90 | |
| CIE flux code | 100/100/100/100/65 | |
| Voeding | 350mA | 500mA |
| | 16Vf | 16.2Vf |
| Opgenomen vermogen | 5.6W | 8.1W |
| Lichtstroom | 488lm | 672lm |
| Rendement | 87lm/W | 83lm/W |
| UGR | | |
| Richtbaarheid | h 360° v 30° | |







Beschikbaar label
<http://supemodular.com/assets/TYPE2.pdf>



THIMBLE 74 ADJUSTABLE LED GE

| ACCESSORIES | |
|-------------|---|
| DRIVER-LED | |
| 12403430 | LED GEAR 350-1050mA 25-50W |
| 12400730 | LED GEAR 500mA 12W |
| 12403730 | LED GEAR 350mA 15W |
| 11630330 | LED GEAR DEEP DIM 350mA 20W 0/1-10V |
| 11630030 | LED GEAR DEEP DIM 350mA 20W DALI |
| 11630430 | LED GEAR DEEP DIM 500mA 20W 0/1-10V |
| 11630130 | LED GEAR DEEP DIM 500mA 20W DALI |
| CONBOX | |
| 11624130 | CONBOX 140X400X100X210 |
| 11624030 | CONBOX 140X250X100X210 |
| HUE-MODULE | |
| 13190130 | HUE DIM CIRCUIT MODULE 150-300W 0/1-10V |
| HUE-BRIDGE | |
| 70000616 | HUE BRIDGE EU |
| 70000617 | HUE BRIDGE UK |
| HUE-DEVICE | |
| 70000615 | HUE TAP SWITCH |
| 70000154 | NIKO PURE SWITCH FOR HUE - WHITE STEEL |
| 70000155 | NIKO PURE SWITCH FOR HUE - BLACK STEEL |
| 70000152 | HUE DIMMER SWITCH |
| 70008054 | HUE SENSOR |



Modular reserves the right to alter material, dimensions and characteristics without prior notice.
Lighting technology changes rapidly. Latest datasheet and documentation available on
www.supermodular.com.