


PUPIL 72 LED GE

Verwacht het onverwachte met Pupil, een armatuur vol verrassingen en tegenstrijdigheden. Met de natuur als zijn muze creëerde de Nederlandse ontwerper Basten Leijh deze eigenzinnige, organische vorm: de neerwaartse verlichting die het omgekeerde doet. Non-conformiteit en functionaliteit gaan hand in hand in onze nieuwe familie, die meer is dan alleen een streling voor het oog.

Art. Nr. 11490109

SPECIFICATIES

Lamp	1x LED Array		
Gear / Transfo	LED gear not incl.		
Inbouwopening	ø 65 h 55		
Gewicht	0.26kg		
Min. afstand	0.1 m		
IP	IP20		
Gloeidraadtest	960°		
Levensduur	L80 B20 @ 50.000 hrs		
CRI	90		
CIE flux code	98/99/100/100/80		
Voeding	350mA	500mA	700mA
	8.5Vf	8.8Vf	9.1Vf
Opgenomen vermogen	3W	4,3W	6,4W
Lichtstroom	275lm	370lm	478lm
Rendement	92lm/W	84lm/W	75lm/W
UGR	18	19	20
Richtbaarheid	h 360° v 60°		





Beschikbaar label
<http://supemodular.com/assets/TYPE2.pdf>

	WARM WHITE 2700K / CRI 90+		WARM WHITE 3000K / CRI 90+	
	MEDIUM 25°	FLOOD 40°	MEDIUM 25°	FLOOD 40°
black struc	11490032	11490332	11490132	11490432
white struc	11490009	11490309	11490109	11490409



PUPIL 72 LED GE

ACCESSORIES	
ANTIGLARE	
14192032	SNOOT Ø26 BLACK
14191032	HONEYCOMB Ø26
14193032	CROSSBLADE Ø26 BLACK
HUE-MODULE	
13190030	MODULAR CONNECTED 1-10V WHITE COMPONENT
HUE-BRIDGE	
70000616	HUE BRIDGE EU
70000617	HUE BRIDGE UK
HUE-DEVICE	
70000152	HUE DIMMER SWITCH
70000154	
70000155	
70000615	HUE TAP SWITCH
70008054	HUE SENSOR



Modular reserves the right to alter material, dimensions and characteristics without prior notice.
Lighting technology changes rapidly. Latest datasheet and documentation available on
www.supermodular.com.