


PUPIL 72 LED GE

Verwacht het onverwachte met Pupil, een armatuur vol verrassingen en tegenstrijdigheden. Met de natuur als zijn muze creëerde de Nederlandse ontwerper Basten Leijh deze eigenzinnige, organische vorm: de neerwaartse verlichting die het omgekeerde doet. Non-conformiteit en functionaliteit gaan hand in hand in onze nieuwe familie, die meer is dan alleen een streling voor het oog.

Art. Nr. 11490132

SPECIFICATIES

| | | | |
|--------------------|----------------------|--------|--------|
| Lamp | 1x LED Array | | |
| Gear / Transfo | LED gear not incl. | | |
| Inbouwopening | ø 65 h 55 | | |
| Gewicht | 0.26kg | | |
| Min. afstand | 0.1 m | | |
| IP | IP20 | | |
| Gloeidraadtest | 960° | | |
| Levensduur | L80 B20 @ 50.000 hrs | | |
| CRI | 90 | | |
| CIE flux code | 100/100/100/100/77 | | |
| Voeding | 350mA | 500mA | 700mA |
| | 8.5Vf | 8.8Vf | 9.1Vf |
| Opgenomen vermogen | 3W | 4,3W | 6,4W |
| Lichtstroom | 265lm | 357lm | 461lm |
| Rendement | 88lm/W | 81lm/W | 72lm/W |
| UGR | 17 | 18 | 19 |
| Richtbaarheid | h 360° v 60° | | |






Beschikbaar label
<http://supemodular.com/assets/TYPE2.pdf>

| | WARM WHITE 2700K / CRI 90+ | | WARM WHITE 3000K / CRI 90+ | |
|-------------|-------------------------------|--------------|-------------------------------|--------------|
| | MEDIUM 25° | FLOOD 40° | MEDIUM 25° | FLOOD 40° |
| black struc | 11490032 | 11490332 | 11490132 | 11490432 |
| white struc | 11490009 | 11490309 | 11490109 | 11490409 |



PUPIL 72 LED GE

| ACCESSORIES | |
|-------------|---|
| ANTIGLARE | |
| 14192032 | SNOOT Ø26 BLACK |
| 14191032 | HONEYCOMB Ø26 |
| 14193032 | CROSSBLADE Ø26 BLACK |
| HUE-MODULE | |
| 13190030 | MODULAR CONNECTED 1-10V WHITE COMPONENT |
| HUE-BRIDGE | |
| 70000616 | HUE BRIDGE EU |
| 70000617 | HUE BRIDGE UK |
| HUE-DEVICE | |
| 70000152 | HUE DIMMER SWITCH |
| 70000154 | |
| 70000155 | |
| 70000615 | HUE TAP SWITCH |
| 70008054 | HUE SENSOR |



Modular reserves the right to alter material, dimensions and characteristics without prior notice.
Lighting technology changes rapidly. Latest datasheet and documentation available on
www.supermodular.com.